




HUA YI CHANG



Emergency Exit Light

C401LEDSC-AU



Item	Model Number	C401LEDSC -AU
	Description	High-brightness LED illuminates in both normal and the event of an emergency
Input	Voltage	110VAC ~ 240VAC
	Frequency	50/60Hz
Output	Light Source	High efficacy LEDX20
	Power Consumption	Fully charged(Standby) 3W (Bat +0.5W)
	Battery	Ni Cd 3.6V 800mAh
	Emergency Duration	Over 2 hours
Physical	Enclosure	Aluminum Alloy
	Mounting	Wall mount or Ceiling mount
	Dimensions L x W x H	410mm x 235mm x 25mm
	Weight	1.21 KG
	IP rating	IP 20
Control	Charger	0.03C ~0.1C trickling charge
	Protection	an overcharge and overcurrent detection circuit, switches off automatically
	Testing	Manual test switch
	Indicator	Red LED lights up when plugged in
Environment	Operating Temperature	5°C to 45°C
	Relative Humidity	0 to 95%

Features	<ol style="list-style-type: none"> 1. The long service life of up to 50,000 hours 2. Light source life is 22 years 3. Injection -molded polycarbonate housing and acrylic diffuser with pictogram legends 4. 24m viewing distance 5. High-density storage LiCoO2 batteries 6. Diffuser & pictogram inserts included 7. Aesthetically pleasing designs 8. Easy to install
----------	--

