




# HUA YI CHANG



## Emergency Exit Light

C402LEDSC-AU



|             |                       |  |
|-------------|-----------------------|--|
| Item        | Model Number          | C402LEDSC -AU  |
|             | Description           | High-brightness LED illuminates in both normal and the event of an emergency |
| Input       | Voltage               | 110VAC ~ 240VAC  |
|             | Frequency             | 50/60Hz  |
| Output      | Light Source          | High efficacy LEDX20   |
|             | Power Consumption     | Fully charged(Standby) 3W (Bat +0.5W)  |
|             | Battery               | Ni Cd 3.6V 800mAh  |
|             | Emergency Duration    | Over 2 hours   |
| Physical    | Enclosure             | Aluminum Alloy   |
|             | Mounting              | Wall mount or Ceiling mount  |
|             | Dimensions L x W x H  | 410mm x 235mm x 25mm   |
|             | Weight                | 1.21 KG  |
|             | IP rating             | IP 20  |
| Control     | Charger               | 0.03C ~0.1C trickling charge   |
|             | Protection            | an overcharge and overcurrent detection circuit, switches off automatically  |
|             | Testing               | Manual test switch   |
|             | Indicator             | Red LED lights up when plugged in  |
| Environment | Operating Temperature | 5°C to 45°C  |
|             | Relative Humidity     | 0 to 95%   |

|          |  |
|----------|--|
| Features | <ol style="list-style-type: none"> <li>1. The long service life of up to 50,000 hours</li> <li>2. Light source life is 22 years</li> <li>3. Injection -molded polycarbonate housing and acrylic diffuser with pictogram legends</li> <li>4. 24m viewing distance</li> <li>5. High-density storage LiCoO2 batteries</li> <li>6. Diffuser &amp; pictogram inserts included</li> <li>7. Aesthetically pleasing designs</li> <li>8. Easy to install</li> </ol> |
|----------|--|

